

Mysql

Primesc o eroare la import-ul bazei de date din backup, ce sa fac?

Daca primiti eroarea `/*!50717 EXECUTE s USING`

`@rocksdb_bulk_load_var_name */;` la importul bazei de date din **backup**

Error

SQL query:

 `/*!50717 EXECUTE s USING @rocksdb_bulk_load_var_name */ ;`

MySQL said: 

#1210 - Incorrect arguments to EXECUTE

Dezarhivati fisierul care contine baza de date si cu un editor text stergeti liniile care incep cu `/*!50717` de la inceputul fisierului Sql.

```
/*!50717 SET @rocksdb_bulk_load_var_name='rocksdb_bulk_load' */;
/*!50717 SELECT COUNT(*) INTO @rocksdb_has_p_s_session_variables FROM
INFORMATION_SCHEMA.TABLES WHERE TABLE_SCHEMA = 'performance_schema' AND
TABLE_NAME = 'session_variables' */;
/*!50717 SET @rocksdb_get_is_supported = IF (@rocksdb_has_p_s_session_variables,
'SELECT COUNT(*) INTO @rocksdb_is_supported FROM
performance_schema.session_variables WHERE VARIABLE_NAME=?', 'SELECT 0') */;
/*!50717 PREPARE s FROM @rocksdb_get_is_supported */;
/*!50717 EXECUTE s USING @rocksdb_bulk_load_var_name */;
/*!50717 DEALLOCATE PREPARE s */;
/*!50717 SET @rocksdb_enable_bulk_load = IF (@rocksdb_is_supported, 'SET SESSION
rocksdb_bulk_load = 1', 'SET @rocksdb_dummy_bulk_load = 0') */;
/*!50717 PREPARE s FROM @rocksdb_enable_bulk_load */;
/*!50717 EXECUTE s */;
/*!50717 DEALLOCATE PREPARE s */;
```

Salvati si reincercati importul.

Mysql

Id-ul solutiei unice: #1301

Autor: : Craciun Calin

Ultima actualizare: 2020-04-06 10:58